

## **TANTO O**


## Surface/Suspension Mounted Ring Luminaire



## Features & Highlights

- IP40 Ingress Protection
- IPO2 Impact Protection
- Matt micro-prismatic polycarbonate diffuser
- Steel housing
- Can be surface or suspension mounted
- Suspension and cable cap options available
- Available with a variety of decorative finishes
- 5 Year warranty (T's & C's apply)
- UK Support

## **Dimensions**



Options & Accessories
5

DALI	/DALI
White (RAL9003S)	/WHI
Grey	/GRY
Black	/BLK
Decorative mesh	/MESH
Suspension kit	/SUSKIT

re Lumens	LL/cW	Colour temp
950	108	840

Part Codes

1	Part Code	Description	Circuit Watts	Luminaire Lumens	LL/cW	Colour temp	
	TAN-CIR-1.2-37-4000-840-WHI	Tanto 1200mm Surface/suspension mounted decorative ring LED 37W ~4,000Lm 108 Lm/CW CRI80 4000K IP40 White	37*	3950	108	840	
	TAN-CIR-1.5-37-4000-840-WHI	As above, <b>1500mm</b> , <b>37w</b> , <b>~4,000Lm 108 Lm/CW</b>	37*	4000	1хх	840	
	TAN-CIR-2-37-5000-840-WHI	As above, 2000mm, 37w, ~5,000Lm 108 Lm/CW	37*	5000	1хх	840	

<sup>\*</sup> Subject to supplier

Please note: Specification values may change due to rapid development of lighting technology. All performance data is taken at an ambient temperature of +25°C. Data may be rounded up/down for illustrative purposes. Tolerance range of optical and electrical data is +/-10%. We reserve the right to amend or change details without prior notification.







